



DOUBLE ACTING
- SINGLE END ROD TYPE (PISTON WITH MAGNET) ... **10S-3R**




Features

- Ultra compact, light weight and space saving cylinder.
- Double acting available.

Specification

Type	10S-3R
Bore	Φ20、25、32、40、50、63
Power fluid	Filtered air with or without lubrication
Proof pressure	15.3 kgf/cm ²
The range of pressure	1 ~ 10.2 kgf/cm ²
The range of temperature	-10 ~ +70 °C (No freezing)
Material of cylinder barrel	Aluminium alloy

How to order

10S-3R	SD	50	N	50	-	T	-	E	2
Type		Bore	Cushion	Stroke		Port thread		Sensor switch	Quantity
 10S-3R		20 : Φ20 25 : Φ25 32 : Φ32 40 : Φ40 50 : Φ50 63 : Φ63	N : No cushion	Please see stroke table		No code : Female thread T : Male thread		E : NR501 F : NR505 U : NS501 X : NS505	1 : 1pc 2 : 2pcs

Stroke table

Bore	Stroke (mm)
Φ20	5,10,15,20,25
Φ25	5,10,15,20,25,30
Φ32	5,10,15,20,25,30,35,40,45,50
Φ40	5,10,15,20,25,30,35,40,45,50
Φ50	5,10,15,20,25,30,35,40,45,50
Φ63	10,15,20,25,30,35,40,45,50

