

## Norminal Size 4

Solenoid pilot actuated  
 Spool with pressure energized soft seals  
 Port size G1/8, manifold system G1/4  
 Operating pressure : 1 to 10 bar

## Features


- Straight manual override with and without detent
- Mounting position optional
- Small size, high flow rate, easy installation
- Exhaust air attenuated
- Common exhaust
- Connector interface to DIN 43650, from B and industrial form
- Low power consumption



## Description (Standard type)

- Solenoid valve for filtered, lubricator\* or non-lubricated air
- Flow direction : Fixed
- Temperature range : -10 °C ~ +60 °C
- Material - Body : Aluminum
- Material - Seat Seal : NBR

## Parameters

Symbol	Cat. No. Valve	Nominal size (ND)	Port size (G)	Operating pressure[bar]		Flow rate QN [l/min]	Switching time* approx.[ms]		Weight [kg]	Solenoid and Connector
				min.	max.		ON	OFF		
	Power consumption 3W (5VA)									
	2630600	4	G1/8	1	10	700	20	20	0.3	See solenoid and connector table
	2630620	4	G1/4	1	10	700	20	20	0.3	

\* Oil recommendation : Shell Hydrol DO 32, Shell Febis K32 (as of July 1992) or compatible oils with DVI values < 8 (DIN53521) and ISO viscosity class 32-46 (DIN51519)

- \* at 6 bar to VDI3290 with DC solenoid
  - Option : Flat Manual override

## How to Order

example : **2630600** · **3052** · **DC24V** X **5**

Valve	Solenoid	Voltage	Quantity
-------	----------	---------	----------

